

Performance Data for Viber® Electric Power Units

Model	Weight pounds	HP	AMP / HP Rating	Plug	Quick Disconnect	Maximum Head Size inches
VMK 1500	13.0	2.5	10 amps	Standard	No	1 ½
VMK 1500 L	13.2	2.5	10 amps	Twist Lock	No	1 ½
VMK 1500 240V	13.0	2.5	6 amps	240 V	No	1 ½
VMK 1500 Q	13.4	2.5	10 amps	Standard	Yes	1 ½
VMK 1500 QL	13.5	2.5	10 amps	Twist Lock	Yes	1 ½
VMK 1500 Q 240V	13.4	2.5	6 amps	240 V	Yes	1 ½
VMK 2500	15.7	2.5	15 amps	Standard	No	1 ¾
VMK 2500 L	15.9	2.5	15 amps	Twist Lock	No	1 ¾
VMK 2500 230V	15.7	2.5	8 amps	230 V	No	1 ¾
VMK 2500 Q	16.1	2.5	15 amps	Standard	Yes	1 ¾
VMK 2500 QL	16.2	2.5	15 amps	Twist Lock	Yes	1 ¾
VMK 2500 Q 240V	16.1	2.5	8 amps	230 V	Yes	1 ¾
VMK 2750	21.6	2.5	15 amps	Standard	No	2 ⅛
VMK 2750 L	21.8	2.5	15 amps	Twist Lock	No	2 ⅛
VMK 2750 240V	21.6	2.5	9 amps	240 V	No	2 ⅛
VMK 2750 Q	22.0	2.5	15 amps	Standard	Yes	2 ⅛
VMK 2750 QL	22.2	2.5	15 amps	Twist Lock	Yes	2 ⅛
VMK 2750 Q 240V	22.0	2.5	9 amps	240 V	Yes	2 ⅛
VMK 3500	24.1	3.0	20 amps	Twist Lock	No	2 ½
VMK 3500 240V	24.1	3.0	12 amps	240 V	No	2 ½
VMK 3500 Q	24.5	3.0	20 amps	Twist Lock	Yes	2 ½
VMK 3500 Q 240V	24.5	3.0	12 amps	240 V	Yes	2 ½